

## **TimbrCORE**

## **Salzburg Collection**

**APPROVED** 



Thickness: 12mm (1/2" nominal)

Core: ULTRACORE™

Finish: High Performance, Scratch Resistant (HPSR)

Wear Rating: AC5 Waterproof: Yes

Bevel: 4-Sided Micro

Gloss: Low

Texture: Embossed In-Register (EIR) Installation: All Grades and Levels Res. Warranty: Limited Lifetime Residential

Com. Warranty: 5-Year Lt. Commercial



GENERAL DATA				
DESCRIPTION	METHOD	RESULT	DETAILS	
Class of Use	EN13329-32	Class 32	All Residential plus general commercial	
Abrasion Resistance	EN13329 (Annex E)	AC5	IP ≥ 5000 cycles	
Impact Resistance	EN13329 (Annex H)	Big Ball: ≥ 1000mm (29.53"), Small Ball: ≥ 5N		
Stain Resistance	EN438-2	Group 1 + 2: Level 5, Group 3: Level 4		
Residual Indentation	EN424	No Visible Damage	Foot Type 0: 1mm /32kg	
Castor Chair Resistance	EN425 (Type W)	No Visible Damage	25,000 cycles	
Thickness Swell Test	ISO 24336	PASSED	≤ 15% (±1%)	
NALFA Surface Swell Test	NALFA LF-01	< 0.3mm	under Grade 2	
Surface Soundness	EN13329 (Annex D)	≥ 1.25 N/mm² / ≥ 0.0019 in²		

	ENVIRONMENTAL CERTIFICATES	
Green Guard	GOLD	
AFFSET	A+	
CARB 2	Compliant	
TSCA Title VI	Compliant	
Content	No heavy metals + lead/cadmium present	
Dangerous Substances	No carcinogenic, mutagenic or reprotoxic substances present (class 1A & 1B)	
Plasticizer	ORTHOPHTHALATES FREE	


















800-325-2625

888-505-7383 herregan.com