

Timbr CORE[™]



APPROVED



Core: ULTRACORE™

Finish: High Performance, Scratch Resistant (HPSR)

Wear Rating: AC4 Waterproof: Yes

Bevel: 4-Sided Micro

Gloss: Low Texture: Timbr

Installation: Angle/Tap on All Grades and Levels

Res. Warranty: Limited Lifetime Residential Com. Warranty: 5-Year Lt. Commercial



GENERAL DATA			
DESCRIPTION	METHOD	RESULT	DETAILS
Class of Use	EN13329-32	Class 32	All Residential plus general commercial
Abrasion Resistance	NALFA LF-01	AC4	IP ≥ 4000 cycles
Impact Resistance	NALFA LF-01	Big Ball: ≥ 1000mm, Small Ball: ≥ 200mm	
Stain Resistance	NALFA LF-01	< 20	No more than slight effect
Sound Transmission	ASTM E90, E413	drop ceiling: STC60 no drop ceiling: STC51	152mm slab
Impact Insulation Class IIC	ASTM E429, E989	drop ceiling: IIC63 no drop ceiling: IIC52	152mm slab
Thickness Swell Test	NALFA-01	PASSED	≤ 16% (±1%)
NALFA Surface Swell Test	NALFA LF-01	< 0.5mm	Passed

	ENVIRONMENTAL CERTIFICATES	
Green Guard	GOLD	
CARB 2	Compliant	
TSCA Title VI	Compliant	
Content	No heavy metals + lead/cadmium present	
Dangerous Substances	No carcinogenic, mutagenic or reprotoxic substances present (class 1A & 1B)	
Plasticizer	ORTHOPHTHALATES FREE	















800-325-2625

888-505-7383 herregan.com

Detroit, MI