PARAMOUNT
FLOORING

SPECIFICATION SHEET

Collection:	Signature WPC
Plank Size:	9” x 60” (228mm x 1520mm)
Gauge:	10mm (0.31”) (including pad)
Pad:	2.0mm IXPE Pad
Finish:	HPSR Urethane with Ceramic Bead
Wear-layer:	20mil
Bevel:	Painted Bevel
Gloss:	Matte
Embossing:	Real Grain+ or EIR
Installation:	All Grades and Levels, Uniclic
Warranty:	25-Year Residential / 10-Year Commercial

PLANK PACKAGING

PCS / CTN:	6
SQFT / CTN:	22.38
CTNs / PLT:	52
PLTs /CAN:	14

PARAMOUNT *Signature*

Technical Data

DESCRIPTION	STANDARD	RESULT	REQUIREMENT
Thickness	ASTM F386	PASSED	±0.005 in.
Wear Layer Thickness	ASTM F410	PASSED	Commercial: ≥20mil (0.5mm)
Size / Square	ASTM F2421	PASSED	±0.016” lf / ≤0.010”
Residual Indentation	ASTM F1914-18	0.02mm (max)	Avg. = ≤ 8% / Max = ≤ 10%
Dimensional Stability	ASTM F2199-20	MD = 0.00% / AMD = -0.01% , Curling max 0.27mm	
Resistance to Chemicals	ASTM F925-13	All Reagents = 0 reaction	No More the slight Change
Castor Chair Resistance	NALFA LF 01-2011 Sec 3.9	no visible damage (25,000 rev)	NA
Static Load Resistance	ASTM F970-17	0.04mm (1000 psi)	±0.005in (0.13) 250 lbs. Load
Coefficient of Friction (Slip Resistance)	ASTM D1028-07	Dry = 0.93 / Wet = 0.64	>0.5 (ASTM & OSHA) >0.6 (ADA Recommended)
Airborne Sound Transmission Loss	ASTM E90	STC = 63	HUD 50
Impact Sound Transmission	ASTM E492	IIC = 62	HUD 50
Critical Radiant Flux	ASTM E648	0.91 watts/cm² (Class 1)	Class I: ≥0.45 W/cm² Class II: ≥0.22 W/cm²
Density		1.00 g/cm3	

Indoor Air Quality (IAQ) Criteria

ASSURE CERTIFIED RIGID CORE FLOORING™

CERTIFIED BY SCS Global Services

This product is Assure™ Certified and has thus been found to comply with the CDPH Standard Method v1.2 testing, ASTM F3261-17 characteristics testing for composition, size, tolerance, product thickness, and wear layer thickness, and tested for lead, hexavalent chromium, cadmium, and mercury per test method EPA SW 846 Method 3052 and not exceed the limits of 100 PPM be combined weight.

This product is FloorScore® Certified and has thus been found to comply with the volatile organic compound emissions criteria of the California Section 01350 standard. FloorScore® Certification can also be used as an alternative path to obtaining LEED EQ 4.3 credit.

floor score

CERTIFIED BY SCS Global Services

NO ORTHOPHTHALATES

herregan distributors, inc

PHONE 800-325-2625 FAX 888-505-7383 WWW. herregan.com

Minneapolis/St. Paul, MN | Des Moines, IA | Omaha, NE | Chicago, IL | Milwaukee, WI | Kansas City, MO | St. Louis, MO | Detroit, MI | Oklahoma City, OK